



# P249

## Roving for LFI

### PRODUCT DESCRIPTION

This Advantex® glass roving has a sizing system with a silane coupling agent. It has been designed to provide optimal use for LFI applications (long fiber injection).

The Advantex® glass fiber combines the electrical and mechanical properties of traditional E-glass with the acid corrosion resistance of E-CR glass.

### PRODUCT REFERENCE

- Example : EC 2400 P249
- E : type of glass
- C : type of process, continuous
- 2400/4800 : roving linear weight
- P249 : OCV™ Reinforcements code for sizing system



### FEATURES AND PRODUCT BENEFITS

- Very good runnability even at high speed.
- Easy chopping
- No static electricity
- No fuzz

### TECHNICAL CHARACTERISTICS (NOMINAL VALUES)

LINEAR WEIGHT (TEX)	LOSS ON IGNITION (%)	MOISTURE (%)
ISO 1889: 1997	ISO 1887: 1995	ISO 3344: 1997
2400/4800	1.40	≤ 0.20

# P249

## Roving for LFI

### PRODUCT AVAILABILITY (STANDARD REFERENCE)

PRODUCT	CHARACTERISTICS OF CHEESES			
	Diameter (mm)		Height (mm)	Net Weight (kg)
Internal	External			
EC 2400/4800 P249	75	280	260	20.5

### PACKAGING

- Each cheese of P249 is protected by a non shrink-wrap polythene film, which should not be removed when it is used, and is identified by an individual label.
- Airsplice package is available on request

PRODUCT	CHEESE DIAMETER (MM)	PALLET DIMENSIONS L X W (CM)	LEVELS PER PALLET	CHEESES PER LEVEL	TOTAL NUMBER OF CHEESES	VETROCREEL	PALLETS	
						NUMBER OF ENDS	APPROX. HEIGHT (CM)	NET WEIGHT* (KG)
EC 2400/4800 P249	280	114 x 114	3/4	16	48/64	1-2-4-16	93/119	984/1312

\* Add 35 to 45 kg to obtain gross weight.

### STORAGE

The P249 roving should be stored in its original packaging in a dry and cool place. Best conditions are at temperature from 10 to 35°C and humidity between 35 and 85%. If you store the product at lower temperatures, please move the soon-to-be-processed pallets to the production area 24 hours ahead of time. You can stock pallets one on one with a plywood plank between the two.

#### Contact

MultiEndRovings.ocvamericas@owenscorning.com

MultiEndRovings.ocvemea@owenscorning.com

MultiEndRovings.ocvap@owenscorning.com



## OCV™ Reinforcements

**OWENS CORNING  
COMPOSITE MATERIALS, LLC**  
ONE OWENS CORNING PARKWAY  
TOLEDO, OHIO 43659  
1.800.GET.PINK™  
www.owenscorning.com  
www.ocvreinforcements.com

**EUROPEAN OWENS CORNING  
FIBERGLAS, SPRL.**  
166, CHAUSSÉE DE LA HULPE  
B-1170 BRUSSELS  
BELGIUM  
+32.2.674.82.11

**OWENS CORNING - OCV ASIA PACIFIC  
SHANGHAI REGIONAL HEADQUARTERS**  
2F OLIVE LVO. MANSION  
620 HUA SHAN ROAD  
SHANGHAI 200040  
CHINA  
+86.21.62489922

This information and data contained herein is offered solely as a guide in the selection of a reinforcement. The information contained in this publication is based on actual laboratory data and field test experience. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application to determine its suitability before committing to production. It is important for the user to determine the properties of its own commercial compounds when using this or any other reinforcement. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe any patent or violate any law safety code or insurance regulation.